High Speed A6 Format Scanner
fi-60F

fi-60F

EUROPEAN ISV PARTNER

AP ASSURANCE PROGRAMME

- Scans A6 format documents in 1 second (b/w and grayscale at 200 dpi)
- Ultra compact design (145 x 234 x 40 mm)
- Maximum scanning area A6 (105 x 148 mm)
- Auto-cropping and auto de-skew (even with open lid)
- High speed USB 2.0 interface
- Fujitsu TWAIN and ISIS drivers included

FUJITSU

THE POSSIBILITIES ARE INFINITE

fi-60F
Revolutionising single document flatbed scanning

fi-60F

The ultra-compact fi-60F from Fujitsu has been especially developed for easy and quick scanning of single documents. With interference-free convenience the fi-60F redefines small document scanning.

Ultra compact and fast
The fi-60F weighs less than 1kg and has an impressively small footprint of only 145 x 234 mm meaning it is ideally suited for even the smallest desktop, reception, check-in desk or cashier booth.

Incredibly fast, the fi-60F can scan a document in gray-scale in just one second at 200dpi and can produce colour images in less than 1½ seconds. Documents at sizes of up to 105 x 148 mm (A6 format) can be scanned at resolutions of up to 600dpi enabling a clear scanned reproduction of even images and photographs. Power consumption is less than 8W in operation and less than 2W in standby mode.

Image enhancement
As documents are scanned so a host of image enhancement features get to work. The user no longer needs to align the scanned document: simply place the document on the flatbed and scan. Any misalignment will be straightened up on the displayed scan, equally automatic cropping ensures that the original size of the document appears on screen without a white border.

Applications
The fi-60F can efficiently be used as a front office device for scanning passports, IDs, prescriptions, driving licences, customer and medical cards or any type of small format document that will then be immediately processed by the installed software application.

Hotel check-ins, post offices, border control and immigration are a few examples of where the fi-60F can help aid every day processes and reduce time consuming activity such as photocopying away from the desk or writing down details for any type of automatic passport, ID card and visa authentication and processing.

Similarly the airline industry could find the fi-60F an easy to deploy device for speeding up check-in and boarding as well as for retrieving passenger records.

The scanner is a convenient device for the banking and financial sector for use on front desks enabling the operator not to have to move from their seat to scan documents. It can be used for POS solutions in mobile phone shops, for medical offices and pharmacies as well as for car rental and leasing business applications.

Additionally in industries with a high turnover of staff particularly from migrant populations it is now government legislation in an increasing number of countries that records of the employees identity are authenticated, processed and stored. The fi-60F provides a simple, compact solution to an ever-increasing requirement.

The fi-60F works via a USB 2.0 interface. Integrators and application developers can take full control of the unit via Fujitsu's TWAIN and ISIS drivers. An optional SDK is also available for the fi-60F's TWAIN based integration.

TWAIN
Linking Images With Applications

POWERED BY
ISIS
PIXEL TRANSLATIONS

Compliant
RoHS
Product

ENERGY STAR

Model	Flatbed		
Document cover	Included (removable) with black pad colour		
Image sensor type	Colour CIS (Contact Image Sensor) (CMOS CIS)		
Light source	R,G,B LED (variable light source)		
Optical resolution	600 dpi		
Output resolution	Colour (24 bit), Grayscale (8 bit), Mono (1 bit): 50 to 600 dpi (settings can be adjusted in 1 dpi increments)		
Scanning speed	Colour at 150 dpi	approx. 1.3 seconds	
	Grayscale at 200 dpi	approx. 1 second	
	Monochrome at 200 dpi	approx. 1 second	
Document size	Maximum A6 (148 x 105 mm)		
Interface	High Speed USB 2.0 (USB 1.1 supported)		
Connector shape	USB (B type)		
Image processing	Image emphasis, simplified DTC, error diffusion, dither, moire removal, auto de-skew, auto-cropping, dropout colour (R, G, B, None)		
Voltage	AC 100 - 240 V, +10% / -10%		
Power	Operating	Less than 8 W	
	Sleep mode	Less than 2 W	
Operating environment	Temperature	5℃ - 35℃	
	Relative humidity	20% - 80% (non-condensing)	
Dimensions (H x W x D)	40 x 145 x 234 mm		
Weight	0.9 kg		
Bundled software	Fujitsu TWAIN driver, ScandAll 21, ISIS™ driver, QuickScan (Trial), Fujitsu Image Processing Software Option (Trial)		

All names, manufacturer names, brand and product designations are subject to special trademark rights and are manufacturer's trademarks and/or registered brands of their respective owners. All indications are non-binding. Technical data is subject to change without prior notification.

FUJITSU

THE POSSIBILITIES ARE INFINITE