

Kodak

i3000 Series Scanners

**Delivering efficiency,
information, and results
with every scan.**



Kodak i3000 Series Scanners

Technical specifications

Recommended Daily Volume	i3200: Up to 15,000 pages per day / i3400: Up to 20,000 pages per day
Throughput Speeds (landscape, letter/A4 size, black and white/greyscale/colour)	i3200: Up to 50 ppm/100 ipm at 200 dpi and 300 dpi i3400: Up to 80 ppm/160 ipm at 200 dpi and 300 dpi (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.)
Scanning Technology	Dual CCD; Greyscale output bit depth is 256 levels (8-bit); colour capture bit depth is 48 bits (16 x 3); colour output bit depth is 24 bits (8 x 3)
Illumination	Dual LED
Operator Control Panel	Graphical LCD display with four operator control buttons
Optical Resolution	600 dpi
Output Resolution	100 / 150 / 200 / 240 / 300 / 400 / 600 / 1200 dpi
Max. / Min. Document Width	Auto-feed: 305 mm / 63.5 mm; Hand-feed: 305 mm / 50 mm
Max. / Min. Document Length	Auto-feed: 863.6 mm / 63.5 mm; Hand-feed: 863.6 mm / 50 mm (rear exit only) Long document mode: 4.1 meters maximum length (The scanners support continuous scanning mode)
Paper Thickness and Weight	34-413 g/m ² paper
Feeder/Elevator	Up to 250 sheets of 80 g/m ² paper
Paper Path Options	Documents can exit into the front output tray, or at the rear of the scanner if the straight-through paper path option is manually selected
Document Sensing	Ultrasonic multi-feed detection; Intelligent Document Protection
Connectivity	USB 2.0 (compatible with USB 3.0-supported PCs); USB 3.0 cable included
Software Support	Fully supported by Kodak Capture Pro Software and Kodak Asset Management Software Bundled TWAIN , ISIS , and WIA drivers; Kodak Capture Desktop Software ; Smart Touch (Linux SANE and TWAIN drivers available from www.kodak.com/go/scanonlinux)
Imaging Features	Perfect Page Scanning; iThresholding; adaptive threshold processing; deskew; autocrop; relative cropping; aggressive cropping; electronic colour dropout; dual stream scanning; interactive colour, brightness and contrast adjustment; automatic orientation; automatic colour detection; intelligent background colour smoothing; intelligent image edge fill; image merge; content-based blank page detection; streak filtering; image hole fill; sharpness filter; auto brightness; special document mode; toggle patch; auto photo cropping; segmented bitonal images
File Format Outputs	Single and multi-page TIFF, JPEG, RTF, BMP, PDF, searchable PDF
Limited Warranty	Three years (Advance Unit Replacement); optional next business day on-site service*
Accessories (Optional)	Kodak Legal Size Flatbed Accessory ; Document imprinting accessory (rear-side, post-scan imprinting of up to 40 alphanumeric characters, with 11 imprinting positions) Kodak A3 Size Flatbed Accessory (available June 2013)
Electrical Requirements	100-240 V (International); 50-60 Hz
Power Consumption	Off mode: <0.5 watts; Running: <75 watts; Sleep mode: <4.5 watts
Environmental Factors	Energy Star qualified scanners; Operating temperature: 15-35° C; Operating humidity: 15% to 76% RH
Acoustical Noise (operator position sound pressure level)	Off or Ready mode: 27 dB(A) Operating mode: <59 dB(A)
Recommended PC Configuration	Intel Core 2 Duo , 2.66 GHz each core (or equivalent), 3 GB RAM
Supported Operating Systems	Windows XP SP3 (32-bit and 64-bit), Windows Vista SP2 (32-bit and 64-bit), Windows 7 SP1 (32-bit and 64-bit), Windows 8 (32-bit and 64-bit), Linux (for details see www.kodak.com/go/scanonlinux)
Approvals and Product Certifications	AS/NZS CISPR 22:2009 + A1:2010 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950-1-07 (C-UL Mark), Canada ICES-003 Issue 5 (Class B), GB4943.1:2011, GB9254:2008 (Class B), GB17625.1:2003 Harmonics (CCC "S&E" Mark), EN 55022:2010 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024:2010 ITE Immunity (CE Mark), EN 60950-1:2006 + A11, A12, A1 (TUV GS Mark), IEC 60950-1, CISPR 22:2008 (Class B), VCCI V3/2012.04 (Class B), CNS 13438:2006 (Class B), CNS 14336-1 (BSMI Mark), UL 60950-1:07 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark
Consumables Available	Roller cleaning pads, Staticide wipes, consumables kit (includes feed module, separation module, separation pad, front transport rollers)
Dimensions	Weight: 15.8 kg Depth: 371 mm with input tray closed Width: 431.8 mm Height: 237.5 mm

*There may be Geographical limitations to the availability of Service. For full details please contact your reseller of Kodak products or your local Service&Support organisation. Kodak enables customers to capture and use valuable information from electronic and paper documents. Our document imaging solutions include award-winning scanners and capture software, and industry-leading service and support. From small offices to global operations, Kodak has the right solution to feed your business the information it needs.



To learn more:

Visit www.kodak.com/go/i3000Series
Produced using Kodak Technologies.



For further information, please see how to contact us at:
<http://www.kodak.com/go/dicontact>